

MarCal 30 EWRI / 30 EWR

Digital Depth Gauge

FUNCTIONS 30 EWRI

- ON/OFF
- AUTO-ON / OFF
- RESET (set display to zero)
- mm/inch
- PRESET (for entering a numerical value)
- LOCK function (key lock)
- HOLD (storage of measured values)
- Reversal of counting direction
- DATA (data transmission)



30 EWRI

FUNCTIONS 30 EWR

- AUTO-ON / OFF
- DATA (data transmission via connection cable)
- ON/OFF
- PRESET (for entering a numerical value)
- RESET (set display to zero)
- mm/inch
- LOCK function (key lock)
- High contrast analog display
- Locking screw above
- Lapped guideway
- Measuring surfaces made of steel
- Slide and beam made of hardened stainless steel
- Immediate measurements due to the Reference System
- Raised guideway for the protection of the scale
- Excellent resistance against dust, coolants and lubricants
- Dirt wipers are integrated in the slide




30 EWR

TECHNICAL DATA

Order no.	Type	Measuring range		Numerical increment	Error limit		Standard
		mm	inch		mm	inches (text)	
4126755	30 EWRI	0 -150	0 -6"	0.01 / .0005"	0.03	.001"	Factory standard
4126754	30 EWRI	0 -200	0 -8"	0.01 / .0005"	0.03	.001"	Factory standard
4126756	30 EWRI	0 -300	0 -12"	0.01 / .0005"	0.04	.0015"	Factory standard
4126757	30 EWRI	0 -500	0 -20"	0.01 / .0005"	0.05	.002"	Factory standard
4126700	30 EWR	0 -150	0 -6"	0.01 / .0005"	0.03	.001"	Factory standard
4126699	30 EWR	0 -200	0 -8"	0.01 / .0005"	0.03	.001"	Factory standard
4126701	30 EWR	0 -300	0 -12"	0.01 / .0005"	0.04	.0015"	Factory standard
4126702	30 EWR	0 -500	0 -20"	0.01 / .0005"	0.05	.002"	Factory standard


Order no.	a b	
	mm	mm
4126755	234	100
4126754	284	100
4126756	384	150
4126757	584	150
4126700	234	100
4126699	284	100
4126701	384	150
4126702	584	150




i-Stick

ACCESSORIES

Order no.	For measuring instrument	Quantity	unit	Product name	Type
4102220	30 EWRI			Receiver for instruments with integrated wireless	i-Stick
4102357	30 EWR			16 EXu data connection cable USB (2 m)	16 EXu
4102410	30 EWR			Data connection cable RS232C (2 m)	16 EXr
4102520	30 EWRI, 30 EWR			Battery 3 V, CR 2032	
4102915	30 EWR			Digimatic data cable (2 m)	16 EWD
4125611	30 EWRI, 30 EWR	Piece		Anvil (4 mm)	30 ESa
4126510	30 EWRI, 30 EWR			Cross beam extension (300 mm)	30 EXm
4126511	30 EWRI, 30 EWR			Cross beam extension (200 mm)	30 EXm



30 EXm



30 ESa