




WTX – High-performance drill, DIN 6537

▲ Specialist for difficult to machine materials

SIG 140°
Solid carbide

10 787 ...

DC _{m7} mm	DCONMS _{h6} mm	OAL mm	LCF mm	LU mm	LS mm	
3,00	6	66	28	23	36	030
3,10	6	66	28	23	36	031
3,20	6	66	28	23	36	032
3,30	6	66	28	23	36	033
3,40	6	66	28	23	36	034
3,50	6	66	28	23	36	035
3,60	6	66	28	23	36	036
3,70	6	66	28	23	36	037
3,80	6	74	36	29	36	038
3,90	6	74	36	29	36	039
3,97	6	74	36	29	36	900
4,00	6	74	36	29	36	040
4,10	6	74	36	29	36	041
4,20	6	74	36	29	36	042
4,23	6	74	36	29	36	901
4,30	6	74	36	29	36	043
4,40	6	74	36	29	36	044
4,50	6	74	36	29	36	045
4,60	6	74	36	29	36	046
4,70	6	74	36	29	36	047
4,80	6	82	44	35	36	048
4,90	6	82	44	35	36	049
5,00	6	82	44	35	36	050
5,10	6	82	44	35	36	051
5,20	6	82	44	35	36	052
5,30	6	82	44	35	36	053
5,40	6	82	44	35	36	054
5,50	6	82	44	35	36	055
5,56	6	82	44	35	36	902
5,60	6	82	44	35	36	056
5,70	6	82	44	35	36	057
5,80	6	82	44	35	36	058
5,90	6	82	44	35	36	059
6,00	6	82	44	35	36	060
6,10	8	91	53	43	36	061
6,20	8	91	53	43	36	062
6,30	8	91	53	43	36	063
6,35	8	91	53	43	36	903
6,40	8	91	53	43	36	064
6,50	8	91	53	43	36	065
6,60	8	91	53	43	36	066
6,70	8	91	53	43	36	067
6,80	8	91	53	43	36	068
6,90	8	91	53	43	36	069
7,00	8	91	53	43	36	070
7,10	8	91	53	43	36	071
7,20	8	91	53	43	36	072
7,30	8	91	53	43	36	073
7,40	8	91	53	43	36	074
7,50	8	91	53	43	36	075
7,60	8	91	53	43	36	076

10 787 ...



DC _{m7} mm	DCONMS _{h6} mm	OAL mm	LCF mm	LU mm	LS mm	
7,70	8	91	53	43	36	077
7,80	8	91	53	43	36	078
7,90	8	91	53	43	36	079
7,94	8	91	53	43	36	904
8,00	8	91	53	43	36	080
8,10	10	103	61	49	40	081
8,20	10	103	61	49	40	082
8,30	10	103	61	49	40	083
8,40	10	103	61	49	40	084
8,50	10	103	61	49	40	085
8,60	10	103	61	49	40	086
8,70	10	103	61	49	40	087
8,80	10	103	61	49	40	088
8,90	10	103	61	49	40	089
9,00	10	103	61	49	40	090
9,10	10	103	61	49	40	091
9,20	10	103	61	49	40	092
9,30	10	103	61	49	40	093
9,40	10	103	61	49	40	094
9,50	10	103	61	49	40	095
9,53	10	103	61	49	40	905
9,60	10	103	61	49	40	096
9,70	10	103	61	49	40	097
9,80	10	103	61	49	40	098
9,90	10	103	61	49	40	099
10,00	10	103	61	49	40	100
10,10	12	118	71	54	45	101
10,20	12	118	71	54	45	102
10,30	12	118	71	54	45	103
10,40	12	118	71	54	45	104
10,50	12	118	71	54	45	105
10,60	12	118	71	54	45	106
10,70	12	118	71	54	45	107
10,80	12	118	71	54	45	108
10,90	12	118	71	54	45	109
11,00	12	118	71	54	45	110
11,10	12	118	71	54	45	111
11,11	12	118	71	54	45	906
11,20	12	118	71	54	45	112
11,30	12	118	71	54	45	113
11,40	12	118	71	54	45	114
11,50	12	118	71	54	45	115
11,60	12	118	71	54	45	116
11,70	12	118	71	54	45	117
11,80	12	118	71	54	45	118
11,90	12	118	71	54	45	119
12,00	12	118	71	54	45	120
12,10	14	124	77	58	45	121
12,20	14	124	77	58	45	122
12,30	14	124	77	58	45	123
12,40	14	124	77	58	45	124
12,50	14	124	77	58	45	125
12,60	14	124	77	58	45	126
12,70	14	124	77	58	45	907
12,80	14	124	77	58	45	128
12,90	14	124	77	58	45	129
13,00	14	124	77	58	45	130
13,10	14	124	77	58	45	131
13,20	14	124	77	58	45	132
13,30	14	124	77	58	45	133
13,40	14	124	77	58	45	134
13,50	14	124	77	58	45	135
13,60	14	124	77	58	45	136
13,70	14	124	77	58	45	137
13,80	14	124	77	58	45	138
13,90	14	124	77	58	45	139

P	○
M	●
K	
N	
S	●
H	
O	

→ v_c Page 109

WTX – High-performance drill, DIN 6537

▲ Specialist for difficult to machine materials



DRAGONSKIN



SIG 140°

Solid carbide

10 787 ...

DC _{m7} mm	DCONMS _{h6} mm	OAL mm	LCF mm	LU mm	LS mm	
14,0	14	124	77	58	45	140
14,1	16	133	83	61	48	141
14,2	16	133	83	61	48	142
14,3	16	133	83	61	48	143
14,4	16	133	83	61	48	144
14,5	16	133	83	61	48	145
14,6	16	133	83	61	48	146
14,7	16	133	83	61	48	147
14,8	16	133	83	61	48	148
14,9	16	133	83	61	48	149
15,0	16	133	83	61	48	150
15,1	16	133	83	61	48	151
15,2	16	133	83	61	48	152
15,3	16	133	83	61	48	153
15,4	16	133	83	61	48	154
15,5	16	133	83	61	48	155
15,6	16	133	83	61	48	156
15,7	16	133	83	61	48	157
15,8	16	133	83	61	48	158
15,9	16	133	83	61	48	159
16,0	16	133	83	61	48	160
16,1	18	143	93	69	48	161
16,2	18	143	93	69	48	162
16,3	18	143	93	69	48	163
16,4	18	143	93	69	48	164
16,5	18	143	93	69	48	165
16,6	18	143	93	69	48	166
16,7	18	143	93	69	48	167
16,8	18	143	93	69	48	168
16,9	18	143	93	69	48	169
17,0	18	143	93	69	48	170
17,1	18	143	93	69	48	171
17,2	18	143	93	69	48	172
17,3	18	143	93	69	48	173
17,4	18	143	93	69	48	174
17,5	18	143	93	69	48	175
17,6	18	143	93	69	48	176
17,7	18	143	93	69	48	177
17,8	18	143	93	69	48	178
17,9	18	143	93	69	48	179
18,0	18	143	93	69	48	180
18,1	20	153	101	75	50	181
18,2	20	153	101	75	50	182
18,3	20	153	101	75	50	183
18,4	20	153	101	75	50	184
18,5	20	153	101	75	50	185
18,6	20	153	101	75	50	186
18,7	20	153	101	75	50	187
18,8	20	153	101	75	50	188
18,9	20	153	101	75	50	189
19,0	20	153	101	75	50	190

10 787 ...

DC _{m7} mm	DCONMS _{h6} mm	OAL mm	LCF mm	LU mm	LS mm	
19,1	20	153	101	75	50	191
19,2	20	153	101	75	50	192
19,3	20	153	101	75	50	193
19,4	20	153	101	75	50	194
19,5	20	153	101	75	50	195
19,6	20	153	101	75	50	196
19,7	20	153	101	75	50	197
19,8	20	153	101	75	50	198
19,9	20	153	101	75	50	199
20,0	20	153	101	75	50	200

P	○
M	●
K	
N	
S	●
H	
O	

→ v_c Page 109