

Performances

Page Pagina 43



| NFE 66052 • ISO 10898 | | | 90° | 90° | 120° | 90° | 120° | 90° | 120° |
|-----------------------|----------|----------|----------------|----------------|----------------|-------------|-------------|---------------|---------------|
| D h6 * | L ± 1 | ℓ + 1 | Classic 190 | magafor 195 | magafor 196 | TiN 0895 | TiN 0896 | Red'X 0995 | Red'X 0996 |
| 2,0 | 49 | 8 | € | € | € | € | € | € | € |
| 3,0 | 50 | 10 | • | • | • | • | • | • | • |
| 3,17 (1/8") | 50 | 10 | • | • | • | • | • | • | • |
| 4,0 | 52 | 12 | • | • | • | • | • | • | • |
| 4,76 (3/16") | 60 | 15 | • | • | • | • | • | • | • |
| 5,0 | 60 | 15 | • | • | • | • | • | • | • |
| 6,0 | 66 | 20 | • | • | • | • | • | • | • |
| 6,35 (1/4") | 66 | 22 | • | • | • | • | • | • | • |
| 7,93 (5/16") | 79 | 25 | • | • | • | • | • | • | • |
| 8,0 | 79 | 25 | • | • | • | • | • | • | • |
| 9,52 (3/8") | 89 | 25 | • | • | • | • | • | • | • |
| 10,0 | 89 | 25 | • | • | • | • | • | • | • |
| 12,0 | 102 | 30 | • | • | • | • | • | • | • |
| 12,70 (1/2") | 102 | 35 | • | • | • | • | • | • | • |
| 14,0 | 115 | 35 | • | • | • | • | • | • | • |
| 15,87 (5/8") | 115 | 35 | • | • | • | • | • | • | • |
| 16,0 | 115 | 35 | • | • | • | • | • | • | • |
| 18,0 | 130 | 40 | • | • | • | • | • | • | • |
| 19,05 (3/4") | 131 | 40 | • | • | • | • | • | • | • |
| 20,0 | 131 | 40 | • | • | • | • | • | • | • |
| 25,0 | 138 | 45 | • | • | • | • | • | • | • |
| 25,4 (1") | 138 | 45 | • | • | • | • | • | • | • |

* Code 190 = h7

Vidéo on line
www.magafor.com



magafor, Le choix! The choice! La elección! La scelta!

| Matière Material Materiale | HSS | HSS-E Cobalt | HSS-E Cobalt + TiN | HSS-E Cobalt + Red'X | CARBURE METALLO DURO | CARBIDE + Hard'X |
|--|--|--|--|--|-------------------------|----------------------|
| Dureté Hardness Durezza | 63 HRC | 65 HRC | 65 HRC + 2300 HV | 65 HRC + 3500 HV | 1800 HV | 1800 HV + 3500 HV |
| Utilisation Use Utilización Impiego | Petites séries Small series Pequeñas series Piccole serie | Production intensive Intensive production Producción intensiva Produzione intensiva | Alliages durs et abrasifs Hard and abrasive alloys Aleaciones duras y abrasivos Leghe dure e abrasive | Aciers trempés Treated steels Aceros tratados Acciai temprati | | |
| Page Pagina | 35-39-41 | 35 ~ 41 | 35-35-41 | 34-37-40 | | |

Promo-kits



magafor

| COMPOSITION | COMPOSICIÓN | COMPOSIZIONE: 1 pièce / pieza / pezzo Ø 4 - 5 - 6 - 8 - 10 - 12 | | | | |
|-------------|-------------|---|------|-------|-----------|--------|
| TYPE | TIPO | magafor | TiN | Red'X | magaforce | Hard'X |
| 90° | Code | 195 | 0895 | 0995 | 8195 | 8195-H |
| 120° | Code | 196 | 0896 | 0996 | 8196 | 8196-H |
| | € | • | • | • | • | • |