


# ER precision collet

- ▲ DIN ISO 15488-B (old DIN 6499-B)
- ▲ Double taper collet
- ▲ 16 times slotted

**ER-B**  
**20 µm**



DCONWS mm	BD = 17 OAL = 27,5 426 E / ER16	BD = 21 OAL = 31,5 428 E / ER20	BD = 26 OAL = 34 430 E / ER25	BD = 33 OAL = 40 470 E / ER32	BD = 41 OAL = 46 472 E / ER40
	Article no. 82 673 ...	Article no. 82 674 ...	Article no. 82 675 ...	Article no. 82 676 ...	Article no. 82 677 ...
1	01000	01000 <sup>1)</sup>			
2	02000	02000 <sup>1)</sup>	02000 <sup>1)</sup>		
3	03000	03000	03000	03000	03000
4	04000	04000	04000	04000	04000
5	05000	05000	05000	05000	05000
6	06000	06000	06000	06000	06000
7	07000	07000	07000	07000	07000
8	08000	08000	08000	08000	08000
9	09000	09000	09000	09000	09000
10	10000	10000	10000	10000	10000
11		11000	11000	11000	11000
12		12000	12000	12000	12000
13		13000	13000	13000	13000
14			14000	14000	14000
15			15000	15000	15000
16			16000	16000	16000
17				17000	17000
18				18000	18000
19				19000	19000
20				20000	20000
21					21000
22					22000
23					23000
24					24000
25					25000
26					26000
Set in wooden box	99900	99900	99900	99900	99900

1) Not included in the set

**i** Clamping range covered: up to Ø 3 mm = 0.5 mm, from Ø 4 mm = 1 mm