


WPC – Högprestandaborr, Verksnorm

≤ 8xD



UNI

TiAIN



HA

135°
Solid HM

T1

DC _{h7}	DCONMS _{h6}	OAL	LCF	LU	LS	Artikel-nr. 11 612 ...	EUR
3,0	6	72	34	29	36	81,99	030
3,1	6	72	34	29	36	81,99	031
3,2	6	72	34	29	36	81,99	032
3,3	6	72	34	29	36	81,99	033
3,4	6	72	34	29	36	81,99	034
3,5	6	72	34	29	36	81,99	035
3,6	6	72	34	29	36	81,99	036
3,7	6	72	34	29	36	81,99	037
3,8	6	81	43	36	36	81,99	038
3,9	6	81	43	36	36	81,99	039
4,0	6	81	43	36	36	81,99	040
4,1	6	81	43	36	36	81,99	041
4,2	6	81	43	36	36	81,99	042
4,3	6	81	43	36	36	81,99	043
4,4	6	81	43	36	36	81,99	044
4,5	6	81	43	36	36	81,99	045
4,6	6	81	43	36	36	81,99	046
4,7	6	81	43	36	36	81,99	047
4,8	6	95	57	48	36	81,99	048
4,9	6	95	57	48	36	81,99	049
5,0	6	95	57	48	36	81,99	050
5,1	6	95	57	48	36	81,99	051
5,2	6	95	57	48	36	81,99	052
5,3	6	95	57	48	36	81,99	053
5,5	6	95	57	48	36	81,99	055
5,8	6	95	57	48	36	81,99	058
5,9	6	95	57	48	36	81,99	059
6,0	6	95	57	48	36	81,99	060
6,1	8	114	76	64	36	101,10	061
6,2	8	114	76	64	36	101,10	062
6,3	8	114	76	64	36	101,10	063
6,5	8	114	76	64	36	101,10	065
6,6	8	114	76	64	36	101,10	066
6,8	8	114	76	64	36	101,10	068
7,0	8	114	76	64	36	101,10	070
7,4	8	114	76	64	36	101,10	074
7,5	8	114	76	64	36	101,10	075
7,7	8	114	76	64	36	101,10	077
7,8	8	114	76	64	36	101,10	078
7,9	8	114	76	64	36	101,10	079
8,0	8	114	76	64	36	101,10	080
8,1	10	142	95	80	40	124,60	081
8,2	10	142	95	80	40	124,60	082
8,3	10	142	95	80	40	124,60	083
8,5	10	142	95	80	40	124,60	085
8,6	10	142	95	80	40	124,60	086
8,7	10	142	95	80	40	124,60	087
8,8	10	142	95	80	40	124,60	088
9,0	10	142	95	80	40	124,60	090
9,1	10	142	95	80	40	124,60	091
9,2	10	142	95	80	40	124,60	092
9,3	10	142	95	80	40	124,60	093
9,4	10	142	95	80	40	124,60	094

DC _{h7}	DCONMS _{h6}	OAL	LCF	LU	LS	T1 Artikel-nr. 11 612 ...	EUR
9,5	10	142	95	80	40	124,60	095
9,7	10	142	95	80	40	124,60	097
9,8	10	142	95	80	40	124,60	098
9,9	10	142	95	80	40	124,60	099
10,0	10	142	95	80	40	124,60	100
10,2	12	162	114	96	45	165,40	102
10,5	12	162	114	96	45	165,40	105
10,8	12	162	114	96	45	165,40	108
11,0	12	162	114	96	45	165,40	110
11,2	12	162	114	96	45	165,40	112
11,5	12	162	114	96	45	165,40	115
11,8	12	162	114	96	45	165,40	118
12,0	12	162	114	96	45	165,40	120
12,5	14	178	131	112	45	248,00	125
13,0	14	178	131	112	45	248,00	130
13,5	14	178	131	112	45	248,00	135
14,0	14	178	131	112	45	248,00	140
14,5	16	203	152	128	48	324,10	145
15,0	16	203	152	128	48	324,10	150
15,5	16	203	152	128	48	324,10	155
16,0	16	203	152	128	48	324,10	160
16,5	18	222	171	144	48	419,90	165
17,0	18	222	171	144	48	419,90	170
17,5	18	222	171	144	48	419,90	175
18,0	18	222	171	144	48	419,90	180
18,5	20	243	190	160	50	467,40	185
19,0	20	243	190	160	50	467,40	190
20,0	20	243	190	160	50	467,40	200

Stål	●
Rostfritt	○
Gjutjärn	●
Icke-järn metaller	○
Värmebeständiga legeringar	○

→ v_c sida 118